



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/015,188	11/19/2001	Risto Wichman	460-010710-US(PAR)	6378
2512	7590	07/16/2004		
PERMAN & GREEN 425 POST ROAD FAIRFIELD, CT 06824			EXAMINER FOX, BRYAN J	
			ART UNIT	PAPER NUMBER
			2686	
			DATE MAILED: 07/16/2004	

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

10/015,188

Applicant(s)

WICHMAN ET AL.

Examiner

Bryan J Fox

Art Unit

2686

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 19 November 2001.
- 2a) ☐ This action is FINAL. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-22 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-4,6-14 and 16-22 is/are rejected.
- 7) ☒ Claim(s) 5 and 15 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☒ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date 2,3.
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____.
- 5) ☐ Notice of Informal Patent Application (PTO-152)
- 6) ☐ Other: _____.

DETAILED ACTION

Specification

The following guidelines illustrate the preferred layout for the specification of a utility application. These guidelines are suggested for the applicant's use.

Arrangement of the Specification

As provided in 37 CFR 1.77(b), the specification of a utility application should include the following sections in order. Each of the lettered items should appear in upper case, without underlining or bold type, as a section heading. If no text follows the section heading, the phrase "Not Applicable" should follow the section heading:

- (a) TITLE OF THE INVENTION.
- (b) CROSS-REFERENCE TO RELATED APPLICATIONS.
- (c) STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT.
- (d) INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC (See 37 CFR 1.52(e)(5) and MPEP 608.05. Computer program listings (37 CFR 1.96(c)), "Sequence Listings" (37 CFR 1.821(c)), and tables having more than 50 pages of text are permitted to be submitted on compact discs.) or
REFERENCE TO A "MICROFICHE APPENDIX" (See MPEP § 608.05(a). "Microfiche Appendices" were accepted by the Office until March 1, 2001.)
- (e) BACKGROUND OF THE INVENTION.
 - (1) Field of the Invention.
 - (2) Description of Related Art including information disclosed under 37 CFR 1.97 and 1.98.
- (f) BRIEF SUMMARY OF THE INVENTION.
- (g) BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S).
- (h) DETAILED DESCRIPTION OF THE INVENTION.
- (i) CLAIM OR CLAIMS (commencing on a separate sheet).
- (j) ABSTRACT OF THE DISCLOSURE (commencing on a separate sheet).
- (k) SEQUENCE LISTING (See MPEP § 2424 and 37 CFR 1.821-1.825. A "Sequence Listing" is required on paper if the application discloses a nucleotide or amino acid sequence as defined in 37 CFR 1.821(a) and if the required "Sequence Listing" is not submitted as an electronic document on compact disc).

The headings separating the various sections are missing. Please add headings to the sections as explained above.

The title of the invention is not descriptive. A new title is required that is clearly indicative of the invention to which the claims are directed.

The following title is suggested: Method of Transmitting Information in a Communication System Using the Same Training Sequence in Various Antennas with Different Phase.

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

There are a number of 112, second paragraph issues, including the following:

Claims 8, 9, 11, 18 and 19 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claims 8 and 18 contain equations with a number of different variables however the variables are not defined in the claims rendering them indefinite. All of the variables and functions need to be clearly defined or the equation loses its meaning. All of the S variables need to be clearly defined as well as k and the functions $\text{tr}\{\}$ and arg .

Claim 9 recites the limitation "said receiving device" in line 18, however line 17 refers to "two or more receiving devices". There is insufficient antecedent basis for this limitation in the claim.

Claim 11 recites the limitation "said at least two antennas" in line 30. There is insufficient antecedent basis for this limitation in the claim.

Claim 19 recites the limitation "said receiving device" in lines 8-9; however, line 7 refers to "two or more receiving devices". There is insufficient antecedent basis for this limitation in the claim.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

Claims 1-4, 6, 11-14, 16, 21 and 22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lindoff et al (US006700882B1).

Regarding claim 1, Lindoff et al discloses a system where a first mobile station is connected to a base station in a particular cell in a TDMA system. The uplink from the MS A to the BS takes place on a carrier frequency f1 and can carry uplink data D0(UL) and the training sequence TS A (see column 3, lines 1-21), which reads on the claimed "method for transmitting information in a communication system comprising at least a mobile communication network in which information is transferred from one or more

transmitting devices to one or more receiving devices at least one training sequence is used in the information transfer". Lindoff et al further discloses that in one embodiment, the MS A may have two antennas 230 and 730 for transmitting signals to the BS, which also may have two antennas 210 and 220 (see figure 9 and column 8, lines 24-33), which reads on the claimed "signals transmitted through at least two antennas are received in the receiving device". Lindoff et al also discloses that the MS may use the same training sequence TS A transmitted from both antennas (see figure 9). In this embodiment, however, Lindoff et al fails to expressly disclose in this embodiment that the same training sequence is transmitted with a different phase.

Lindoff et al also discloses in another embodiment uplink sequences are transmitted with different phase-offsets, so a first information sequence has a $\phi(0)$ and a second information sequence has a different phase offset $\phi(1)$ (see column 6, lines 16-34 and figure 5B).

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the first discussed embodiment with the second discussed embodiment so that the MS with two different antennas transmits the same training sequence but with different phases in order to best take advantage of the benefits of the invention, such as increased spectrum efficiency (see column 2, lines 16-17). Also, the combining of various embodiments in full or in part is suggested by Lindoff et al (see column 8, lines 50-64).

Regarding claim 2, Lindoff et al discloses that different information may be transmitted from two different antennas (see column 8, lines 24-33 and figure 8B),

Art Unit: 2686

which reads on the claimed “the transferred information is divided to be transmitted through at least two antennas to the receiving device”. The receiving section at the mobile station receives a signal and converts it to a baseband signal as is known in the art. The baseband signal is fed from the block 404 to a synchronization unit 406 that correlates the received sequence with the known training sequences (TS A and TS B) in order to find a synchronization position, which is used with the received burst to estimate the radio channels for the signals (see figure 4 and column 4, lines 17-50). Lindoff et al then discloses that the receiver structure in the BS (which would be used in the uplink from MS to BS) is similar to the structure in the MS with the exception that the BS has an antenna array (see column 5, lines 44-49), which reads on the claimed “in the receiving device, an examination is performed for the transmitted information using signals transmitted through different antennas”.

Regarding claim 3, Lindoff et al discloses that the transmitting device is a mobile station MS (see figure 9), which reads on the claimed “network element”, and the receiving device is a base station BS (see figure 9), which reads on the claimed “wireless communication device”.

Regarding claim 4, Lindoff et al discloses that different signals may be transmitted through different antennas (see figure 8B), and describes the differentiation of signals at the mobile station (see column 4, line 43 – column 5, line 6), then explains that the receiving at the base station is the same as that at the mobile station (see column 5, lines 44-49).

Regarding claim 6, Lindoff et al discloses that the system is a TDMA system and that the training sequence TS A is transmitted in each burst for synchronization and radio channel estimation purpose (see column 3, lines 1-22), which reads on the claimed "the information is transmitted in data frames, which are supplemented with said training sequence".

Regarding claim 11, Lindoff et al discloses a system where a first mobile station is connected to a base station in a particular cell in a TDMA system. The uplink from the MS A to the BS takes place on a carrier frequency f_1 and can carry uplink data D0(UL) and the training sequence TS A (see column 3, lines 1-21), which reads on the claimed "communication system comprising at least one transmitting device, at least one receiving device, means for transmitting information from the transmitting device to at least one receiving device, in which transmission at least one training sequence is used". Lindoff et al further discloses that in one embodiment, the MS A may have two antennas 230 and 730 for transmitting signals to the BS, which also may have two antennas 210 and 220 (see figure 9 and column 8, lines 24-33), which reads on the claimed "the receiving device comprises means for the reception of the signal transmitted through said at least two antennas". Lindoff et al discloses that the system is TDMA and that the training sequence is included in each burst (see column 3, lines 1-21), so the information is transmitted in data frames as claimed. Lindoff et al also discloses that the MS may use the same training sequence TS A transmitted from both antennas (see figure 9). In this embodiment, however, Lindoff et al fails to expressly

disclose in this particular embodiment that the same training sequence is transmitted with a different phase.

Lindoff et al also discloses in another embodiment uplink sequences are transmitted with different phase-offsets, so a first information sequence has a $\phi(0)$ and a second information sequence has a different phase offset $\phi(1)$ (see column 6, lines 16-34 and figure 5B).

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the first discussed embodiment with the second discussed embodiment so that the MS with two different antennas transmits the same training sequence but with different phases in order to best take advantage of the benefits of the invention, such as increased spectrum efficiency (see column 2, lines 16-17). Also, the combining of various embodiments in full or in part is suggested by Lindoff et al (see column 8, lines 50-64).

Regarding claim 12, Lindoff et al discloses that different information may be transmitted from two different antennas (see column 8, lines 24-33 and figure 8B), which reads on the claimed "the information to be transferred is divided to be transmitted through at least two antennas to the receiving device". The receiving section at the mobile station receives a signal and converts it to a baseband signal as is known in the art. The baseband signal is fed from the block 404 to a synchronization unit 406 that correlates the received sequence with the known training sequences (TS A and TS B) in order to find a synchronization position, which is used with the received burst to estimate the radio channels for the signals (see figure 4 and column 4, lines 17-

Art Unit: 2686

50). Lindoff et al then discloses that the receiver structure in the BS (which would be used in the uplink from MS to BS) is similar to the structure in the MS with the exception that the BS has an antenna array (see column 5, lines 44-49), which reads on the claimed "the receiving device comprises means for examining the transmitted information using signals transmitted through different antennas".

Regarding claim 13, Lindoff et al discloses that the transmitting device is a mobile station MS (see figure 9), which reads on the claimed "network element", and the receiving device is a base station BS (see figure 9), which reads on the claimed "wireless communication device".

Regarding claim 14, Lindoff et al discloses that different signals may be transmitted through different antennas (see figure 8B), and describes the differentiation of signals at the mobile station (see column 4, line 43 – column 5, line 6), then explains that the receiving at the base station is the same as that at the mobile station (see column 5, lines 44-49).

Regarding claim 16, Lindoff et al discloses that the system is a TDMA system and that the training sequence TS A is transmitted in each burst for synchronization and radio channel estimation purpose (see column 3, lines 1-22), which reads on the claimed "means for transmission of information in data frames, which are supplemented with said training sequence".

Regarding claim 21, Lindoff et al discloses a system where a first mobile station is connected to a base station in a particular cell in a TDMA system. The uplink from the MS A to the BS takes place on a carrier frequency f_1 and can carry uplink data

D0(UL) and the training sequence TS A (see column 3, lines 1-21), which reads on the claimed "network element to be used in a communication system, comprising means for transmitting information from the network element to a wireless device, in which the transmission uses at least one training sequence". Lindoff et al further discloses that in one embodiment, the MS A may have two antennas 230 and 730 for transmitting signals to the BS, which also may have two antennas 210 and 220 (see figure 9 and column 8, lines 24-33), which reads on the claimed "network information is transmitted with at least two antennas". Lindoff et al discloses that the system is TDMA and that the training sequence is included in each burst (see column 3, lines 1-21), so the information is transmitted in data frames as claimed. Lindoff et al also discloses that the MS may use the same training sequence TS A transmitted from both antennas (see figure 9). In this embodiment, however, Lindoff et al fails to expressly disclose in this particular embodiment that the same training sequence is transmitted with a different phase.

Lindoff et al also discloses in another embodiment uplink sequences are transmitted with different phase-offsets, so a first information sequence has a $\phi(0)$ and a second information sequence has a different phase offset $\phi(1)$ (see column 6, lines 16-34 and figure 5B).

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the first discussed embodiment with the second discussed embodiment so that the MS with two different antennas transmits the same training sequence but with different phases in order to best take advantage of the benefits of the

invention, such as increased spectrum efficiency (see column 2, lines 16-17). Also, the combining of various embodiments in full or in part is suggested by Lindoff et al (see column 8, lines 50-64).

Regarding claim 22, Lindoff et al discloses a system where a first mobile station is connected to a base station in a particular cell in a TDMA system. The uplink from the MS A to the BS takes place on a carrier frequency f_1 and can carry uplink data $D_0(UL)$ and the training sequence TS A (see column 3, lines 1-21), which reads on the claimed "wireless communication device be used in a communication system, comprising at least one network element, means for transmitting information from the network element to a wireless communication device, in which the transmission uses at least one training sequence". Lindoff et al further discloses that in one embodiment, the MS A may have two antennas 230 and 730 for transmitting signals to the BS, which also may have two antennas 210 and 220 (see figure 9 and column 8, lines 24-33), which reads on the claimed "information is transmitted by using at least two antennas, wherein the wireless communication device comprises means for reception of the signal transmitted through said at least two antennas". Lindoff et al discloses that the system is TDMA and that the training sequence is included in each burst (see column 3, lines 1-21), so the information is transmitted in data frames as claimed. The receiving section at the mobile station receives a signal and converts it to a baseband signal as is known in the art. The baseband signal is fed from the block 404 to a synchronization unit 406 that correlates the received sequence with the known training sequences (TS A and TS B) in order to find a synchronization position, which is used with the received burst to

estimate the radio channels for the signals (see figure 4 and column 4, lines 17-50). Lindoff et al then discloses that the receiver structure in the BS (which would be used in the uplink from MS to BS) is similar to the structure in the MS with the exception that the BS has an antenna array (see column 5, lines 44-49), which reads on the claimed "the wireless communication device comprises means for performing channel correction on the basis of the signal transmitted by at least two different antennas and received by the wireless communication device". Lindoff et al also discloses that the MS may use the same training sequence TS A transmitted from both antennas (see figure 9). In this embodiment, however, Lindoff et al fails to expressly disclose in this particular embodiment that the same training sequence is transmitted with a different phase.

Lindoff et al also discloses in another embodiment uplink sequences are transmitted with different phase-offsets, so a first information sequence has a $\phi(0)$ and a second information sequence has a different phase offset $\phi(1)$ (see column 6, lines 16-34 and figure 5B).

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the first discussed embodiment with the second discussed embodiment so that the MS with two different antennas transmits the same training sequence but with different phases in order to best take advantage of the benefits of the invention, such as increased spectrum efficiency (see column 2, lines 16-17). Also, the combining of various embodiments in full or in part is suggested by Lindoff et al (see column 8, lines 50-64).

Claims 7 and 17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lindoff et al as applied to claims 1 and 11 above, and further in view of Guan (US005440347A).

Regarding claims 7 and 17, Lindoff et al fails to expressly disclose that the phase shift of training signals is chosen to minimize the interference between the training sequences.

Guan discloses a system to minimize interference in digital transmissions where a training sequence inverter 20 acts to aperiodically invert selected training sequences in order to avoid the periodicity which results in the undesired interference, and the inversion of a sequence, in terms of complex representation, represents a 180 degree rotation (see column 3, lines 32-40), which reads on the claimed invention where the phase shift of the training sequence is defined by minimizing the interference between the training sequences.

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify Lindoff et al with Guan in order to avoid as much as possible the problems caused by interference such as distortion.

Claims 9, 10, 19 and 20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lindoff et al as applied to claims 1 and 11 above, and further in view of Persson et al (US005577047A).

Regarding claims 9 and 19, Lindoff et al fails to expressly disclose that the transmitting device, or mobile station, is in connection with two or more receiving devices, or base stations, as claimed.

Persson et al discloses a system for providing soft handover in a TDMA (see column 4, lines 3-20).

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify Lindoff et al with Persson et al to include the above soft handover in the TDMA system in order to take advantage of the benefits of soft handover, such as no interruption of traffic whatsoever as disclosed by Persson et al (see column 2, lines 25-34). The resultant combination would have a mobile station, or transmitter, that may be connected to two base stations, or receivers, as claimed.

Regarding claims 10 and 20, the same training sequence is used in the mobile station (see rejection of claims 1 and 11 above). Since it is the same training sequence, it must be part of the same training sequence family and reads on the claimed "for one network element one of said training sequences is selected at a time".

Allowable Subject Matter

Claims 5 and 15 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

The following is a statement of reasons for the indication of allowable subject matter:

Regarding claims 5 and 15, the prior art applied fails to teach, suggest or render obvious a method for transmitting information in a communication system using at least one training sequence and signals are transmitted through at least two antennas are received in the receiving device, wherein a different phase of the same training sequence is used in data frames transmitted through different antennas and the information is divided to be transmitted through at least two antennas to the receiving device with an examination performed for the transmitted information at the receiving device using signals transmitted through different antennas and signals transmitted by at least two wireless communication devices are received, and different phases of the same training sequence are used in at least two of the wireless communication devices.

Conclusion

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure:

Hottinen et al (US005995499A) discloses signal detection in a TDMA system.

Langlet et al (US005930248A) discloses a radio communication system selectively using multicast with variable offset time.

Dabak et al (US 20040101032A1) discloses space time transmit diversity for TDD/WCDMA systems.

Dolle et al (US006674817B1) discloses a communication device and distinguishing method for distinguishing between different data burst types in a digital telecommunication system.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Bryan J Fox whose telephone number is (703) 305-8994. The examiner can normally be reached on Monday through Friday 9-5.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Marsha Banks-Harold can be reached on (703) 305-4379. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

BJF


7/12/09
LESTER G. KINCAID
PRIMARY EXAMINER